

Sōlus Series

HOT New Carpet Extractors from U.S. Products

The ultimate in user friendly design, the Sōlus is engineered for one person operation and transport. Upright design with large rear wheels and roller handles make the Sōlus very easy to transport up and down stairs and in and out of a work van by one person. Enhanced performance features include, dual 3-stage or 2-stage, top mounted vacuums for incredible water recovery. Three different models offer adjustable 0-500, variable 300/75, or fixed 150 psi and give the operator the power and versatility needed for the toughest jobs. A key new feature is the optional solution re-circulator. Turn on the re-circulator and pre-heat the water in the tank up to 125 degrees. The Sōlus uses the standard patented in-line heating system delivering instant heat, but by raising the temperature of the water in the tank we have significantly increased consistent heat and cleaning power. The Sōlus brings together all the best innovations of the U.S. Products line into one easy to use portable carpet extractor. Put this powerhouse to work for you today!



Sōlus 500*

The Sōlus 500 and 500R are the first portable carpet extractors to receive the GOLD rating from CRI's Seal of Approval Program. U.S. Products extractors are the only portable extractors available that have achieved the GOLD rating from CRI. Fully adjustable 0-500 psi. Solid state circuitry combined with an inline heater provides instant heat of 212° F at the wand tip, fully adjustable. Low moisture design and 12 gallon capacity provides longer run times. NEW optional tank preheat re-circulates solution and raises temperature up to 125° F in the tank. Patented circuit locator prevents blown circuits. Dual, top-mounted 3-stage vacuums provide superior water recovery.



Sōlus 310*

Variable 300/75 psi for carpet or upholstery cleaning. Inline heater provides instant heat of 212° F at the wand tip. Low moisture design and 12 gallon capacity. NEW optional tank preheat re-circulates solution and raises temperature up to 125° F in the tank. Patented circuit locator prevents blown circuits. Dual, top-mounted 2-stage vacuums. Upright, dolly design, roller handles, and large rear wheels for easy maneuvering on stairs or loading and unloading by one person.

**The Solus 500(R) and 310(r) have been tested and awarded the Gold certification for superior cleaning performance from Carpet and Rug Institute's Seal of Approval Program.*



Sōlus 150

Excellent value with performance features including 150 psi, dual 2-stage vacuums. Inline heater provides instant heat of 212° F at the wand tip. Low moisture design and 12 gallon capacity. Upright, dolly design, roller handles, and large rear wheels for easy maneuvering on stairs or loading and unloading by one person.



Heated Carpet Extractor

U
S
P
R
O
D
U
C
T
S

Sōlus Series

HOT New Carpet Extractors from U.S. Products

Exclusive Features From U.S. Products

- **Dual Top Mounted Vacuums:** Soft-start, with unrestricted airflow for superior water recovery, 3-stage in parallel for the 500 and 2-stage in parallel for the 310 and 150.
- **Heater Element:** In-line, after the pump for longer life and instant heat up to 212 °F at the wand tip, lifetime warranty.
- **Low Moisture System:** Less water combined with higher heat means faster drying, less chance of shrinkage or wicking from the pad.
- **Smart Circuit Locator:** Identifies separate lines to eliminate blown circuits.
- **Tanks & Bodies:** Lightweight, rotationally molded with lifetime warranty against cracks, leaks and dents.
- **Optional Solution Pre-Heat:** Re-circulates solution through the heater to raise the solution temperature up to 125°F for constant heat (500 & 310 models only).
- **Solid-State Circuitry:** Senses temperature change in heat exchanger within 1 degree F for more consistent heat at the tip (500 & 310 Series Only).

Specifications

	<u>Sōlus 500*</u>	<u>Sōlus 310*</u>	<u>Sōlus 150</u>
Vacuum	Dual 5.7", 3-stage soft start vacs, in parallel	Dual 2-stage 5.7" vacs soft start vacs, in parallel	Dual 2-stage 5.7" vacs soft start vacs, in parallel
Vac Shutoff	Electronic	Electronic	Electronic
Pump	Positive Displacement fully adjustable 0-500 psi	Positive displacement 300 psi carpet 75 psi upholstery	Demand pump 150 psi
Heat	Instant, Adjustable to 212 °F	Instant to 212 °F	Instant to 212 °F
Heater	2000 Watts	2000 Watts	2000 Watts
Gauge	Glycerin filled pressure gauge	Glycerin filled pressure gauge	N/A
Wand	Evolution Rotationally Molded twin tip, 500 psi	Evolution Rotationally Molded twin tip, 300 psi	Stainless Steel Single Bend twin tip
Weight	108 lbs.	110 lbs.	102 lbs.
Pre-Heat	Optional re-circulator for for 125°F solution temp. (500R)	Optional re-circulator for for 125°F solution temp. (310R)	NA
CSA/ETL	CSA C22.2 No. 10-1965 R2004	CSA C22.2 No. 10-1965 R2004	NA
Optional	Part #: Solus-500-CSA	Part #: Solus-310-CSA	



Standard Features on all Sōlus Models

- Dimensions: 41"H x 22.5"W x 30"L
- Smart circuit locator
- Solid-state circuitry (500 & 310 Series Only)
- Low moisture design
- 12 gallon solution tank
- 9 gallon recovery tank
- 500 & 310 available with optional solution pre-heat system
- Two handles for easy maneuverability and loading
- Wand caddy for easy transport
- Dump hose, 22" height
- 12" non-marking wheels and upright dolly design for easy stair climbing by a single person
- Convenient low solution filling area for easy filling
- 15' high pressure solution line and crushproof vacuum hose (optional 25' available)
- Cords: Two (2) 25' detachable 12/3 gauge, hospital grade plugs
- Roller handles for easy loading

**The Solus 500(R) and 310(R) have been tested and awarded the Gold certification for superior cleaning performance from Carpet and Rug Institute.*

181 W. Aqua Avenue
 Coeur d'Alene, ID 83815
 Phone: (208) 772-0573
 Toll Free: (800) 257-7982
 Fax: (208) 772-0577
 Web: www.usproducts.com



Heated Carpet Extractor

U
S
P
R
O
D
U
C
T
S